



Maxiglass LG3/150LG low height bottle cooler

LG3/150LG

Maxiglass plug ready glass door bottle cooler

About the product

Maxiglass bottle coolers are packed full of innovations, with larger capacity, brighter lights and energy saving features, this is our best Maxiglass yet

Available to finance with our award-winning [interest-free credit](#) and [leasing options](#) (UK customers only)

Learn more about our [Maxiglass bottle cooler range](#).

Why choose this product

- The MG3 has been engineered with a fully foamed shell, driving significantly improved temperature performance
- Dimmable LED lights create a beautifully illuminated display area, encouraging impulse purchases
- The MG3 is one of the greenest bottle coolers on the market, with up to 30% energy savings compared to the previous range and R600a environmentally friendly refrigerant as standard
- Innovative flat shelving design ensures no more 'wobbly' bottles, allowing effortless stocking and retrieval of drinks
- Low maintenance condenser design reduces the risk of blockages, meaning that the refrigeration system doesn't have to work so hard
- Top mounted door locks are supplied as standard, keeping contents safe and secure

Specification

| Technical | | Dimensions | |
|----------------------|-------------------|--------------------|--|
| Refrigerant | R600A | Height (mm) | 840 |
| Temperature | Refrigerator +6°C | Width (mm) | 602 |
| Electrical supply | 220-240V/50/60/1 | Depth (mm) | 575 |
| Current (A) | 0.6 | Gross volume (ltr) | 125 |
| Power (W) | 95 | Gross weight (kg) | 61 |
| Refrigerant mass (g) | 65 | Net weight (kg) | 55 |
| | | Capacity | 98 x 330ml bottles , 172 x 250ml bottles |

| Build | | Energy | |
|-----------------------------------|-------------------------|-------------------------------|--------|
| Door material | Anthracite frame, glass | Climate Class | CC3 |
| Finish ext/int | | Energy grade | C |
| Maximum number of shelf positions | 2 | EEL | 26.7 |
| Number of sections | 1 | AEC (kWh) | 277 |
| Section configuration | Left hinge | GWP | 3 |
| System | Integral | Min - max temperature (°C) | +2/+18 |
| | | Energy consumption (kWh/24hr) | 0.76 |

Footnotes

- Height is adjustable from 840 to 850mm
- Allow an extra 10mm to the side of the cabinet for optimal airflow
- Depth of the cabinet is excluding handgrip, including power supply connection

Thank you for your interest in this product. We hope you now have everything you need to choose Gamko, however if you have any further questions, please do not hesitate to contact us.

Gamko, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.gamko.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.